

HP Professional Satin Photo Paper

Experience outstanding, heavyweight, resin -coated photo paper for photographic printing



Enjoy high -performance photo printing

Now you can print high -end photography, posters, and retail graphics for either custom or high -volume projects with your HP Latex printer on this versatile resin -coated photo paper.

Move quickly and efficiently through production

There's no need to wait; print and deliver to provide quick turnarounds for your customers. This heavyweight photo paper (275 g/m²) also provides increased stability for handling high volume production. Meet the environmental objectives of your company —and your clients —with this FSC® -certified paper. ¹

Achieve spot -on, dynamic color

The bright-white finish provides a high dynamic range and a wide color gamut for color critical, eye -catching reproductions on a satin finish.

| Target customers | Applications | Benefits | |
|-----------------------------------|--|--|--|
| Point-of-purchase providers | Photo enlargements | Prints come out completely dry, enabling production printing | |
| Trade show and exhibit companies | Art and décor reproductions | Heavy, thick construction for easy handling | |
| Photo and art reproduction houses | Point-of-purchase displays | Wide color gamut and bright-white surface | |
| Technical Specifications | Trade show and event displays | FSC®-certified paper ¹ | |
| Ink compatibility | Compatible with Original HP Latex Inks; also solvent, low-solvent, and UV-curable inks | | |

| Iztapai | apa |
|-----------|--------|
| T. 55 503 | 7 2980 |

T. 33 3825 0964



HP Professional Satin Photo Paper

| Weight | 275 g/m² per ISO 536 Test Method |
|-----------------------|---|
| Thickness | 248 microns/9.8 mil per ISO 534 Test Method |
| Opacity | > 96% per TAPPI T-425 Test Method |
| Brightness | 96 per TAPPI T-452 Test Method |
| Whiteness | 130 per ISO 11475 Test Method |
| Finish | Satin |
| Operating temperature | 15 to 35° C / 59 to 95° F |
| Operating humidity | 30 to 80% RH |
| Dry time | Instant dry |
| Lamination | Yes, cold |
| Shelf life | 1 year, unopened in original packaging |
| Storage temperature | 0 to 40° C / 32 to 104° F |
| Storage humidity | 5 to 95% RH |
| Environmental | FSC®-certified paper ¹ |
| Country of origin | Product of Germany |
| Core size | 3-in core |



The mark of responsible forestry

Ordering Information

| Product Number | Roll Sizes | UPC | Region |
|-----------------------|-----------------------------------|--------------|-----------|
| E4J46A | 914 mm x 30,5 m (36 in x 100 ft) | 848412014501 | Worldwide |
| E4J47A | 1067 mm x 30,5 m (42 in x 100 ft) | 848412014518 | Worldwide |
| E4J48A | 1372 mm x 30,5 m (54 in x 100 ft) | 848412014525 | Worldwide |
| E4J49A | 1524 mm x 30,5 m (60 in x 100 ft) | 848412014532 | Worldwide |

T. 33 3825 0964

Monterrey