


# HP Super Heavyweight Plus Matte Paper



The HP large format printing system-the complete solution

HP large format printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide uncompromising image quality, reliability, and consistency-with every print.



## Produce professional full-color graphics

See highly saturated images that lie flat, smooth When the job requires professional full-color graphics and photo-realistic images this heavy, matte-finish paper—with a barrier layer under a thick top coating that enables ripple-free prints-delivers excellent highlights and rich shadow details.

#### Streamline your workflow

Move quickly and smoothly through post-print processing. Instant-dry, smear-resistant prints—even with high ink densities—enable immediate handling and lamination. Excellent film laminate compatibility helps you keep peak productivity.

#### Create durable prints for a versatile set of jobs

Produce a wide array of graphics-display applications and print with both Original HP pigment- and dye-based inks. Meet the environmental objectives of your company—and your clients-with this FSC®-certified paper.

Target customers	Applications	Benefits		
Print service providers	Trade show and event displays	Highly-saturated, photo-realistic images		
Large retailers	Posters and presentations	Bright white, smooth coating for vivid color contrast		
Graphic designers	POP and retail displays	Flat, smooth prints even under high ink densities		
Ad agencies	Geographic Information Systems (GIS)	n Excellent film laminate compatibility		
Repro houses	Architecture (AEC)	Instant-dry, smear-resistant prints		
Geographic Information Systems (GIS) professionals	Engineering (CAD)	Compatible with both Original HP pigment- and dye- based inks		
Architects		FSC <sup>®</sup> -certified paper <sup>1</sup>		

Izta	pala	pa

T. 55 5037 2980

**Chapultepec** T. 55 5516 5565 T. 55 5516 1432

Guadalajara T. 33 3826 6757 T. 33 3825 0964

Monterrey T. 81 8340 5933 T. 81 8345 5933 Krona

inventa, crea, Imprime 💻 Distribuidor Autorizado de Papeles HP 🖂 dventas@kronaline.com.mx



### **Technical specifications**



HP Super Heavyweight Plus Matte Paper For the latest ICC profiles/paper presets, please visit HPLEMedia.com/hp/paperpresets.

Discrete   227 microns / 10.9 mil per ISO 534 Test Method     Opacity   98% per TAPPI T-452 Test Method     Brightness   99 per TAPPI T-452 Test Method     Whiteness   130 per CIE Ganz 82 Test Method     Finish   Matte     Display permanence (Commercial In-window)   1 year unlaminated, 3 years laminated     Operating temperature   15 to 35° C / 59 to 95° F     Operating temperature   15 to 35° C / 59 to 95° F     Operating temperature   1 stant dry (at 23° C, 50% RH)     Lamination   Yes, compatible with thermal, heat assist, and pressure-sensitive film laminates     Shelf life   1 year, unopened in original packaging     Storage temperature   0 to 40° C / 32 to 104° F     Storage temperature   0 to 40° C / 32 to 104° F     Storage temperature   0 to 40° C / 32 to 104° F     Storage temperature   0 to 40° C / 32 to 104° F     Storage temperature   0 to 40° C / 32 to 104° F     Ordering information   Product of Germany     Ordering information   Qe6228   1067 mm x 30,5 m (42 in	Ink compatibility	Compatible with I	Compatible with both Original HP pigment- and dye-based inks						
Opacity   98% per TAPPI T-425 Test Method     Brightness   99 per TAPPI T-452 Test Method     Whiteness   130 per CIE Ganz 82 Test Method     Finish   Matte     Display permanence (Commercial in-window)   1 year unlaminated, 3 years laminated     Operating temperature   15 to 35° C / 59 to 95° F     Operating temperature   15 to 35° C / 59 to 95° F     Operating temperature   15 to 35° C / 59 to 95° F     Operating humidity   20 to 80% RH     Dry time   Instant dry (at 23° C, 50% RH)     Lamination   Yes, compatible with thermal, heat assist, and pressure-sensitive film laminates     Shelf life   1 year, unopened in original packaging     Storage temperature   0 to 40° C / 32 to 104° F     Storage temperature   0 to 40° C / 32 to 104° F     Storage temperature   Product of Germany     Country of origin   Product of Germany     Ordering information   Product of Germany     Ordering information   Product numbers   Roll sizes   UPC codes   Region     Q66208   104 mm x 30,5 m (36 in x 100 ft)   848412013573   Worldwide     Q66208   1067 mm x 30,5 m (42 in x 100 ft)   848412013573 <td< td=""><td>Weight (without liner)</td><td>224 g/m² per ISO 53</td><td colspan="6">224 g/m² per ISO 536 Test Method, (60 lbs)</td></td<>	Weight (without liner)	224 g/m² per ISO 53	224 g/m² per ISO 536 Test Method, (60 lbs)						
Brightness 99 per TAPPI T-452 Test Method Whiteness 130 per CIE Ganz 82 Test Method Finish Matte Display permanence (Commercial in-window) 1 year unlaminated, 3 years laminated Operating temperature 15 to 35° C / 59 to 95° F Operating temperature 15 to 35° C / 59 to 95° F Operating temperature 15 to 35° C / 59 to 95° F Operating temperature 15 to 35° C / 59 to 95° F Operating temperature 15 to 35° C / 59 to 95° F Operating temperature 15 to 35° C / 59 to 95° F Operating temperature 15 to 35° C / 59 to 95° F Storage temperature 15 to 35° C / 59 to 95° F Storage temperature 0 to 40° C / 32 to 104° F Storage temperature 0 to 40° C / 32 to 104° F Storage temperature 5 to 95% RH Environmental Recyclable through commonly available recycling programs <sup>2</sup> and FSC*-certified paper <sup>1</sup> Country of origin Product of Germany Ordering information Q66268 610 mm x 30,5 m (42 in x 100 ft) 848412013566 Worldwide Q66278 914 mm x 30,5 m (42 in x 100 ft) 848412013573 Worldwide Q66288 1067 mm x 30,5 m (42 in x 100 ft) 848412013573 Worldwide Q66288 1067 mm x 30,5 m (42 in x 100 ft) 848412013580 Worldwide Q66288 1067 mm x 30,5 m (42 in x 100 ft) 848412013580 Worldwide Warranty HP large format printing materials are free from defects in materials and workmanship. For warranty statement ple statement of the structure of the struc	Thickness	227 microns /10.9 r	227 microns /10.9 mil per ISO 534 Test Method						
130 per CIE Ganz 82 Test Method     Finish   Matte     Display permanence (Commercial in-window)   1 year unlaminated, 3 years laminated     Operating temperature   15 to 35° C / 59 to 95° F     Operating humidity   20 to 80% RH     Dry time   Instant dry (at 23° C, 50% RH)     Lamination   Yes, compatible with thermal, heat assist, and pressure-sensitive film laminates     Shelf life   1 year, unopened in original packaging     Storage temperature   0 to 40° C / 32 to 104° F     Storage humidity   5 to 95% RH     Environmental   Recyclable through commonly available recycling programs <sup>2</sup> and FSC*-certified paper <sup>1</sup> Country of origin   Product numbers   Roll sizes   UPC codes   Region     Q66268   610 mm x 30,5 m (24 in x 100 ft)   848412013566   Worldwide     Q66278   914 mm x 30,5 m (36 in x 100 ft)   848412013580   Worldwide     Q6628   1067 mm x 30,5 m (36 in x 100 ft)   848412013597   Worldwide     Q6628   1667 mm x 30,5 m (42 in x 100 ft)   848412013597   Worldwide     Q6628   1067 mm x 30,5 m (42 in x 100 ft)   848412013597   Worldwide     Q66208   1524 mm x 30,5 m (42 in x 100 ft) <td>Opacity</td> <td>98% per TAPPI T-42</td> <td colspan="7">98% per TAPPI T-425 Test Method</td>	Opacity	98% per TAPPI T-42	98% per TAPPI T-425 Test Method						
Finish   Matte     Display permanence (Commercial in-window)   1 year unlaminated, 3 years laminated     Operating temperature   15 to 35° C / 59 to 95° F     Operating humidity   20 to 80% RH     Dry time   Instant dry (at 23° C, 50% RH)     Lamination   Yes, compatible with thermal, heat assist, and pressure-sensitive film laminates     Shelf life   1 year, unopened in original packaging     Storage temperature   0 to 40° C / 32 to 104° F     Storage temperature   0 to 40° C / 32 to 104° F     Storage humidity   5 to 95% RH     Environmental   Recyclable through commonly available recycling programs <sup>2</sup> and FSC*-certified paper <sup>1</sup> Country of origin   Product of Germany     Ordering information   Product numbers   Roll sizes   UPC codes   Region     Q6628B   1067 mm x 30,5 m (36 in x 100 ft)   848412013566   Worldwide     Q6628B   1067 mm x 30,5 m (36 in x 100 ft)   848412013597   Worldwide     Q6630B   1524 mm x 30,5 m (61 in x 100 ft)   848412013597   Worldwide     Warranty   HP large format printing materials are free from defects in materials and workmanship. For warranty statement ple see HLFLMedia.com/mediawarrantites. To obtain warranty service, please contact Brand	Brightness	99 per TAPPI T-452	99 per TAPPI T-452 Test Method						
Display permanence (Commercial in-window)   1 year unlaminated, 3 years laminated     Operating temperature   15 to 35° C / 59 to 95° F     Operating humidity   20 to 80% RH     Dry time   Instant dry (at 23° C, 50% RH)     Lamination   Yes, compatible with thermal, heat assist, and pressure-sensitive film laminates     Shelf life   1 year, unopened in original packaging     Storage temperature   0 to 40° C / 32 to 104° F     Storage temperature   0 to 40° C / 32 to 104° F     Storage humidity   5 to 95% RH     Environmental   Recyclable through commonly available recycling programs <sup>2</sup> and FSC*-certified paper <sup>1</sup> Country of origin   Product of Germany     Ordering information   Product numbers   Roll sizes   UPC codes   Region     Q6628   610 mm x 30,5 m (24 in x 100 ft)   848412013566   Worldwide     Q6628   1067 mm x 30,5 m (36 in x 100 ft)   848412013573   Worldwide     Q66308   1524 mm x 30,5 m (60 in x 100 ft)   848412013580   Worldwide     Q66308   1524 mm x 30,5 m (60 in x 100 ft)   848412013597   Worldwide     Q66308   1524 mm x 30,5 m (60 in x 100 ft)   848412013597   Worldwide     Q	Whiteness	130 per CIE Ganz 82	130 per CIE Ganz 82 Test Method						
(Commercial in-window)   I year Unlaminated, 3 years laminated     Operating temperature   15 to 35° C / 59 to 95° F     Operating humidity   20 to 80% RH     Dry time   Instant dry (at 23° C, 50% RH)     Lamination   Yes, compatible with thermal, heat assist, and pressure-sensitive film laminates     Shelf life   1 year, unopened in original packaging     Storage temperature   0 to 40° C / 32 to 104° F     Storage humidity   5 to 95% RH     Environmental   Recyclable through commonly available recycling programs <sup>2</sup> and FSC*-certified paper <sup>1</sup> Country of origin   Product of Germany     Ordering information   Product of Germany     Ode 6268   610 mm x 30,5 m (24 in x 100 ft)   848412013566     Q66268   106 m x 30,5 m (36 in x 100 ft)   848412013573     Worldwide   Q6628   1052 mm x 30,5 m (42 in x 100 ft)   848412013580     Worldwide   Q66308   1524 mm x 30,5 m (60 in x 100 ft)   848412013597     Warranty   HP large format printing materials are free from defects in materials and workmanship. For warranty statement ple see HBLEMedia.com/mediawarranties. To obtain warrant yservice, please contact Brand Management Group cust	Finish	Matte	Matte						
Operating humidity   20 to 80% RH     Dry time   Instant dry (at 23° C, 50% RH)     Lamination   Yes, compatible with thermal, heat assist, and pressure-sensitive film laminates     Shelf life   1 year, unopened in original packaging     Storage temperature   0 to 40° C / 32 to 104° F     Storage humidity   5 to 95% RH     Environmental   Recyclable through commonly available recycling programs <sup>2</sup> and FSC*-certified paper <sup>1</sup> Country of origin   Product of Germany     Ordering information   Product numbers   Roll sizes   UPC codes   Region     Q6626B   610 mm x 30,5 m (24 in x 100 ft)   848412013566   Worldwide     Q6627B   914 mm x 30,5 m (36 in x 100 ft)   848412013573   Worldwide     Q6628B   1067 mm x 30,5 m (42 in x 100 ft)   848412013573   Worldwide     Warranty   HP large format printing materials are free from defects in materials and workmanship. For warranty statement ple see <u>HPLEMedia.com/mediawarranties</u> . To obtain warranty service, please contact Brand Management Group cust		1 year unlaminated	1 year unlaminated, 3 years laminated						
Dry time   Instant dry (at 23° C, 50% RH)     Lamination   Yes, compatible with thermal, heat assist, and pressure-sensitive film laminates     Shelf life   1 year, unopened in original packaging     Storage temperature   0 to 40° C / 32 to 104° F     Storage humidity   5 to 95% RH     Environmental   Recyclable through commonly available recycling programs ² and FSC*-certified paper 1     Country of origin   Product of Germany     Ordering information   Product of Germany     Ordering information   Product numbers   Roll sizes     Q6626B   610 mm x 30,5 m (24 in x 100 ft)   848412013566   Worldwide     Q6627B   914 mm x 30,5 m (36 in x 100 ft)   848412013573   Worldwide     Q6628B   1067 mm x 30,5 m (60 in x 100 ft)   848412013580   Worldwide     Q6630B   1524 mm x 30,5 m (60 in x 100 ft)   848412013597   Worldwide     Warranty   HP large format printing materials are free from defects in materials and workmanship. For warranty statement ple see HDLEMedia.com/mediawarranties To obtain warranty service, please contact Brand Management Group cust	Operating temperature	15 to 35° C / 59 to 9	15 to 35° C / 59 to 95° F						
Lamination   Yes, compatible with thermal, heat assist, and pressure-sensitive film laminates     Shelf life   1 year, unopened in original packaging     Storage temperature   0 to 40° C / 32 to 104° F     Storage humidity   5 to 95% RH     Environmental   Recyclable through commonly available recycling programs <sup>2</sup> and FSC*-certified paper <sup>1</sup> Country of origin   Product of Germany     Ordering information   Product numbers   Roll sizes   UPC codes   Region     Q66268   610 mm x 30,5 m (24 in x 100 ft)   848412013566   Worldwide     Q6627B   914 mm x 30,5 m (36 in x 100 ft)   848412013573   Worldwide     Q66308   1524 mm x 30,5 m (60 in x 100 ft)   848412013597   Worldwide     Warranty   HP large format printing materials are free from defects in materials and workmanship. For warranty statement ple see HPLEMedia.com/mediawarranties To obtain warranty service, please contact Brand Management Group cust	Operating humidity	20 to 80% RH	20 to 80% RH						
Shelf life   1 year, unopened in original packaging     Storage temperature   0 to 40° C / 32 to 104° F     Storage humidity   5 to 95% RH     Environmental   Recyclable through commonly available recycling programs <sup>2</sup> and FSC*-certified paper <sup>1</sup> Country of origin   Product of Germany     Ordering information   Product numbers   Roll sizes   UPC codes   Region     Q6626B   610 mm x 30,5 m (24 in x 100 ft)   848412013566   Worldwide     Q6627B   914 mm x 30,5 m (36 in x 100 ft)   848412013580   Worldwide     Q6628B   1067 mm x 30,5 m (60 in x 100 ft)   848412013597   Worldwide     Q6630B   1524 mm x 30,5 m (60 in x 100 ft)   848412013597   Worldwide     Warranty   HP large format printing materials are free from defects in materials and workmanship. For warranty statement ple see <u>HPLEMedia.com/mediawarranties</u> . To obtain warranty service, please contact Brand Management Group cust	Dry time	Instant dry (at 23° C	Instant dry (at 23° C, 50% RH)						
Storage temperature   0 to 40° C / 32 to 104° F     Storage humidity   5 to 95% RH     Environmental   Recyclable through commonly available recycling programs <sup>2</sup> and FSC®-certified paper 1     Country of origin   Product of Germany     Ordering information   Product numbers   Roll sizes   UPC codes   Region     Q6626B   610 mm x 30,5 m (24 in x 100 ft)   848412013566   Worldwide     Q6627B   914 mm x 30,5 m (36 in x 100 ft)   848412013573   Worldwide     Q6628B   1067 mm x 30,5 m (42 in x 100 ft)   848412013580   Worldwide     Q6630B   1524 mm x 30,5 m (60 in x 100 ft)   848412013597   Worldwide     Warranty   HP large format printing materials are free from defects in materials and workmanship. For warranty statement ple see HPLEMedia.com/mediawarranties. To obtain warranty service, please contact Brand Management Group cust	Lamination	Yes, compatible wi	Yes, compatible with thermal, heat assist, and pressure-sensitive film laminates						
Storage humidity   5 to 95% RH     Environmental   Recyclable through commonly available recycling programs <sup>2</sup> and FSC*-certified paper <sup>1</sup> Country of origin   Product of Germany     Ordering information   Product numbers   Roll sizes   UPC codes   Region     Q6626B   610 mm x 30,5 m (24 in x 100 ft)   848412013566   Worldwide     Q6627B   914 mm x 30,5 m (36 in x 100 ft)   848412013573   Worldwide     Q6628B   1067 mm x 30,5 m (42 in x 100 ft)   848412013580   Worldwide     Q6630B   1524 mm x 30,5 m (60 in x 100 ft)   848412013597   Worldwide     Warranty   HP large format printing materials are free from defects in materials and workmanship. For warranty statement ple see HPLEMedia.com/mediawarranties To obtain warranty service, please contact Brand Management Group cust	Shelf life	1 year, unopened ir	1 year, unopened in original packaging						
Environmental   Recyclable through commonly available recycling programs <sup>2</sup> and FSC*-certified paper <sup>1</sup> Country of origin   Product of Germany     Ordering information   Product numbers   Roll sizes   UPC codes   Region     Q6626B   610 mm x 30,5 m (24 in x 100 ft)   848412013566   Worldwide     Q6627B   914 mm x 30,5 m (36 in x 100 ft)   848412013573   Worldwide     Q6628B   1067 mm x 30,5 m (42 in x 100 ft)   848412013580   Worldwide     Q6630B   1524 mm x 30,5 m (60 in x 100 ft)   848412013597   Worldwide     Warranty   HP large format printing materials are free from defects in materials and workmanship. For warranty statement ple see HPLFMedia.com/mediawarranties To obtain warranty service, please contact Brand Management Group cust	Storage temperature	0 to 40° C / 32 to 10	0 to 40° C / 32 to 104° F						
Country of origin   Product of Germany     Ordering information   Product numbers   Roll sizes   UPC codes   Region     Q6626B   610 mm x 30,5 m (24 in x 100 ft)   848412013566   Worldwide     Q6627B   914 mm x 30,5 m (36 in x 100 ft)   848412013573   Worldwide     Q6628B   1067 mm x 30,5 m (42 in x 100 ft)   848412013580   Worldwide     Q6630B   1524 mm x 30,5 m (60 in x 100 ft)   848412013597   Worldwide     Warranty   HP large format printing materials are free from defects in materials and workmanship. For warranty statement ple see HPLEMedia.com/mediawarranties. To obtain warranty service, please contact Brand Management Group cust	Storage humidity	5 to 95% RH	5 to 95% RH						
Ordering information   Product numbers   Roll sizes   UPC codes   Region     Q6626B   610 mm x 30,5 m (24 in x 100 ft)   848412013566   Worldwide     Q6627B   914 mm x 30,5 m (36 in x 100 ft)   848412013573   Worldwide     Q6628B   1067 mm x 30,5 m (42 in x 100 ft)   848412013580   Worldwide     Q6630B   1524 mm x 30,5 m (60 in x 100 ft)   848412013597   Worldwide     Warranty   HP large format printing materials are free from defects in materials and workmanship. For warranty statement ple see HPLFMedia.com/mediawarranties To obtain warranty service, please contact Brand Management Group cust	Environmental	Recyclable through	Recyclable through commonly available recycling programs <sup>2</sup> and FSC <sup>®</sup> -certified paper <sup>1</sup>						
Q6626B   610 mm x 30,5 m (24 in x 100 ft)   848412013566   Worldwide     Q6627B   914 mm x 30,5 m (36 in x 100 ft)   848412013573   Worldwide     Q6628B   1067 mm x 30,5 m (42 in x 100 ft)   848412013580   Worldwide     Q6630B   1524 mm x 30,5 m (60 in x 100 ft)   848412013597   Worldwide     Warranty   HP large format printing materials are free from defects in materials and workmanship. For warranty statement ple see HPLFMedia.com/mediawarranties To obtain warranty service, please contact Brand Management Group cust	Country of origin	Product of German	Product of Germany						
Q6627B 914 mm x 30,5 m (36 in x 100 ft) 848412013573 Worldwide   Q6628B 1067 mm x 30,5 m (42 in x 100 ft) 848412013580 Worldwide   Q6630B 1524 mm x 30,5 m (60 in x 100 ft) 848412013597 Worldwide   Warranty HP large format printing materials are free from defects in materials and workmanship. For warranty statement ple see HPLFMedia.com/mediawarranties To obtain warranty service, please contact Brand Management Group cust	Ordering information	Product numbers	Roll sizes	UPC codes	Region				
Q6628B 1067 mm x 30,5 m (42 in x 100 ft) 848412013580 Worldwide   Q6630B 1524 mm x 30,5 m (60 in x 100 ft) 848412013597 Worldwide   Warranty HP large format printing materials are free from defects in materials and workmanship. For warranty statement ple see HPLFMedia.com/mediawarranties To obtain warranty service, please contact Brand Management Group cust		Q6626B	610 mm x 30,5 m (24 in x 100 ft)	848412013566	Worldwide				
Q6630B 1524 mm x 30,5 m (60 in x 100 ft) 848412013597 Worldwide   Warranty HP large format printing materials are free from defects in materials and workmanship. For warranty statement ple see <u>HPL FMedia.com/mediawarranties</u> . To obtain warranty service, please contact Brand Management Group cust		Q6627B	914 mm x 30,5 m (36 in x 100 ft)	848412013573	Worldwide				
Warranty     HP large format printing materials are free from defects in materials and workmanship. For warranty statement ple       see     HPLEMedia.com/mediawarranties.     To obtain warranty service, please contact Brand Management Group cust		Q6628B	1067 mm x 30,5 m (42 in x 100 ft)	848412013580	Worldwide				
see HPLEMedia.com/mediawarranties. To obtain warranty service, please contact Brand Management Group cust		Q6630B	1524 mm x 30,5 m (60 in x 100 ft)	848412013597	Worldwide				
	Warranty	see <u>HPLFMedia.co</u>	HP large format printing materials are free from defects in materials and workmanship. For warranty statement please see <u>HPLFMedia.com/mediawarranties</u> . To obtain warranty service, please contact Brand Management Group custon support at <u>HPLFMedia.com/hp/en/contactus</u> .						

HP has a policy for offering Forest Stewardship Council® (FSC®)-certified papers that are sourced from FSC®-certified forests and other controlled sources. BMG trademark license code FSC®-C115319, see fsc.org. HP trademark license code FSC®-C017543, see fsc.org. Not all FSC®-certified products are available in all regions. Can be recycled through commonly available recycling programs.



Iztapalapa T. 55 5037 2980 Chapultepec T. 55 5516 5565 T. 55 5516 1432

Guadalajara T. 33 3826 6757 T. 33 3825 0964

Monterrey T. 81 8340 5933 T. 81 8345 5933



Distribuidor Autorizado de Papeles HP 🖂 dventas@kronaline.com.mx