

HP PVC-free Wall Paper



The HP large format printing system-the complete solution

HP large format printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide uncompromising image quality, reliability, and consistency—with every print.



Differentiate with PVC-free¹ wall murals

Designed with the environment in mind

Offer odorless displays that are UL GREENGUARD GOLD Certified² and meet AgBB criteria³ using this FSC®-certified paper.4

Be productive—easy to print, install, and remove

Maintain high productivity in your print shop and offer your customers an easy-to-use solution. This wall paper goes up—and comes down—with water, and it comes with an HP warranty.

Boldly define interior spaces—see the ColorPRO difference

See high-impact graphics with an extended range of colors. Engineered with ColorPRO Technology to deliver color excellence, this digital wall mural solution from HP delivers professional quality and striking results.

Target customers	Applications Wall murals	Benefits		
Print service providers		PVC-free ¹ alternative, easier to dispose of than most PVC-based substrates		
	Creative design applications	Mold and mildew resistant ⁵		
		Vivid color, high-definition detail		
		Ultra-smooth finish		
		Prepaste facilitates easy application		
		Strippable and easy to remove, with an HP warranty		
		Flame resistant ⁶		
		Carries the CE mark ⁷ and is UKCA compliant ⁸		
		FSC°-certified paper4		

T. 55 5516 1432



HP PVC-free Wall Paper

Data sheet | HP PVC-free Wall Paper

Technical specifications



HP PVC-free Wall Paper

For the latest ICC profiles/paper presets, please visit HPL FMedia.com/hp/paperpresets.

Ink compatibility	Original HP Latex In	Original HP Latex Inks					
Weight	175 g/m² per ISO 536 Test Method						
Thickness	177 microns/7 mil per ISO 534 Test Method						
Opacity	94% per TAPPI T-425 Test Method						
Brightness	83 per ISO 2470 Test Method						
Whiteness	85 per ISO 11475 Test Method						
Finish	Matte						
Operating temperature	15 to 30° C / 59 to 86° F						
Operating humidity	15 to 80% RH						
Display permanence (Commercial in-window)	Up to 3 years, unlaminated with HP Latex Inks ⁹						
Water resistance	Water resistant with HP Latex Inks ¹⁰						
Flame resistance	Class A, B1, EN 13501, M1, and ISO 5660-1:2002 approved fire certifications ⁶						
Shelf life	1 year, unopened in original packaging						
Storage temperature	15 to 30° C / 59 to 86° F						
Storage humidity	15 to 80% RH						
Environmental	FSC®-certified paper⁴						
Country of origin	Product of United States						
Ordering information	Product numbers	Roll sizes	UPC codes	Region			
	CH098B CH003B CH103A	1067 mm x 30,5 m (42 in x 100 ft) 1372 mm x 30,5 m (54 in x 100 ft) 1372 mm x 91,4 m (54 in x 300 ft)	848412009699 848412009675 848412009682	Worldwide Worldwide Worldwide			
Warranty	HP large format printing materials are free from defects in materials and workmanship. For warranty statement please see HPLFMedia.com/mediawarranties. To obtain warranty service, please contact Brand Management Group customer support at HPLFMedia.com/hp/en/contactus.						

- Based on HP internal and third-party testing chemical analysis that demonstrates elemental chlorine to be at or below 200 ppm. Presence of chlorine is attributed to residual chlorine used in paper-making process, and not due to the presence of PVC.
- 2 HP PVC-free Wall Paper printed with HP Latex Inks is UL GREENGUARD GOLD Certified. UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL'S GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit ulcom/gg or greenguardorg.
- 3 HP PVC-free Wall Paper printed with HP Latex Inks meets AgBB criteria for health-related evaluation of VOC emissions of indoor building products. See umweltbundesamt.de/en/topics/health/ commissions-working-groups/committeefor-health-related-evaluation-of-building.
- 4 HP has a policy for offering Forest Stewardship Council® (FSC®)-certified papers that are sourced from FSC®-certified forests and other controlled sources. BMG trademark license code FSC®-C115319, see <u>fsc.org</u>, HP trademark license code FSC®-C017543, see <u>fsc.org</u>. Not all FSC®-certified products are available in all regions. For information about HP large format printing materials, please visit <u>HPL FMedia.com</u>.
- With HP Latex Inks. UL GREENGUARD found HP PVC-free Wall Paper, which is designed with a breathable construction, to be mold and mildew resistant using test method GGTM.P040 and following the guidelines of ASTM D 6329. See greenguard.org/en/CertificationPrograms_listingprograms_copy1/CertificationPrograms_microbialProgram.aspx. No products are mold proof. It is uncertain that any material will resist mold or mildew indefinitely.
- 6 Class A, B1, EN 13501, M1, and ISO 5660-1:2002 approved fire certifications.
- Self-declared according to European Standard EN15102.
- Self-declared according to European Standard EN15102 and UKCA.
- Interior in-window display ratings by HP Image Permanence Lab on a range of media. HP predictions based on test data under Xenon-Arc illuminant-calculation assumes 6,000 Lux/12 hrs day. For more information, see HPLFMedia.com/t/perintpermanence.
- Performance varies based on printer and print profile. Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see HPLFMedia.com/t/perintpermanence.











Iztapalapa

T. 55 5037 2980

Chapultepec

T. 55 5516 5565

T. 55 5516 1432

Guadalajara

T. 33 3826 6757 T. 33 3825 0964 Monterrey

T. 81 8340 5933 T. 81 8345 5933

